

Part Number: 5899

5899 Thin Client for VDI Performance Class

The 5899 Thin Client is well suited for every user type, right from advanced and task workers, through to the most hostile manufacturing environments. It integrates high-performance and versatility to create the best form factor Thin Client available in today's marketplace, whether you are running published applications or a full VDI implementation. The 5899 Thin Client is designed to be eco-friendly while still delivering an uncompromised VDI experience to the end-user. Heightened security, increased productivity, and centralized management are just a few of the benefits that the 5899 will bring to your desktops.

| ▶ NoTouch OS 2.38 | ▶ Dual DVI Monitor Support STD |
|----------------------------------|------------------------------------|
| ► Ultra-mini form factor | ► Optional 802.11 a/b/g/n Wireless |
| ► VMware & Citrix Ready | ► VESA Mounting Capable |
| ▶ Intel Atom Dual Core Processor | ► Centralized Management |

^{*}Featuring Support for Virtual Bridges & Quest.





















5899 Thin Client for VDI

| System | |
|-----------------|---|
| Management | 10ZiG NoTouch Management Utility |
| Form Factor | Ultra Mini |
| Processor | Intel Atom D2550 Dual Core 1.86GHz |
| Chipset | Intel NM10 Integrated Graphics Media Accelerator 3650 |
| Dimensions | |
| Device | 1.7"(W) x 7.8"(H) x 5.1"(D) - 42mm x 198mm x 140mm |
| Weight | 2.53 lbs (1.15kg) |
| Connections | |
| Ports | USB x 5, Mic-In x 1, Line-Out x 1, PS2 x 1, RJ-45 LAN, DC Jack x 1 |
| Video/Audio | DVI-I x 1 (VGA Supported with Included Adapter), DVI-D x 1, 1920 x 1200 |
| Networking | |
| Wireless | Optional (Internal USB header and mini PCIe socket for WLAN module) |
| Ethernet | 10/100/1000 Base-T |
| Environmental | |
| Operating Temp. | 32-95F (0-35C), 20-80% non-condensing humidity |
| Power | 12 Watt Consumption, 36 Watt, DC-12V/3A External Power Adapter |



SPECIFICATIONS

- 1. Power Button/Power HDD LED
- 2. Front USB (2)
- 3. Mic In
- 4. Line Out
- 5. Secure USB (1)
- 6. Back USB (2)
- 7. Ethernet -RJ45 LAN port
- 8. PS2 port
- 9. DVI-D
- 10. DVI-I
- 11. DC Jack
- 12. Kensington Lock

WARRANTY: All Thin Clients include a 3-Year Advanced Exchange Warranty

5899

Operating System 10ZiG NoTouch (Linux)

| Memory | |
|----------------------------------|--|
| RAM | MIN: 1GB MAX: 2GB |
| Storage | MIN: 1GB MAX: 2GB |
| Software | |
| Software Applications | Firefox, Citrix Receiver, RDP, VNC |
| VDI Connection Brokers Supported | Citrix XenDesktop w/ HDX, VMware Horizon View w/ PCoIP, VDI-In-a-Box, 2X, Quest vWorkspace |





